

# PRODUCT INFORMATION BULLETIN

#### **DESCRIPTION**

**Evencure W30** is a wax-based, sprayable curing compound formulated to cure freshly laid concrete. It is a low to medium viscosity, white pigmented emulsion of specially blended waxes.

**Evencure W30** meets the requirements of AS3799 for moisture retention in liquid membrane curing compounds.

#### **USES**

**Evencure W30** is suitable for curing all freshly laid concrete, either smooth or textured, indoors or outdoors.

NOTE: After thirty to thirty five (30-35) days the continuous film formed on the concrete surface will begin to degrade due to exposure to UV light. The rate of degradation will depend on the initial film thickness and the degree of UV exposure. Evencure W30 can be used as a debonding agent when applied to the concrete sub-base prior to pouring the concrete base. This allows the two layers to expand and contract differentially without producing cracking.

#### **CAUTION**

**EVENCURE W30** WILL NOT TAKE AFTERTRADES. If aftertrades are going to be applied, mechanical removal of **Evencure W30** is required. If unsure, please contact your distributor or the manufacturer for advice.

#### SURFACE APPLICATION

**Evencure W30** can be easily sprayed with most commonly used spraying equipment including bitumen emulsion sprayers. (Requires a minimum pressure of 280kPa [40 psi]).

Apply **Evencure W30** to the concrete as soon as the bleed water has gone and the concrete has hardened sufficiently to not be marked by the application process.

Apply **Evencure W30** undiluted at a rate of 1 litre per 5m<sup>2</sup>. It is best applied by spray, but may also be applied by brush, roller or broom.

**Evencure W30** performs best when one complete coat is applied, until a continuous uniform film is achieved.

1

### TYPICAL PROPERTIES AND APPLICATION DATA

Appearance	White milky liquid
Coverage	5m² per litre
Viscosity	0.02 Pascal seconds
Solids	30% or greater
Solubility in Water	Negligible
Flash Point	100°C
Solvents	5% aromatics
Shelf Life	6 months maximum
Dry Time	- Tack Free: 1 - 3 hours - Hard Dry: 4 - 8 hours - Trafficable: 24 hours
Application Temperature	10°C - 35°C
Application By	- Spray - Brush - Roller - Broom
Packaging	- 205-litre drum - 20-litre container
UN Number	N/A
Hazchem Code	N/A
Packaging Group	N/A
Poison Schedule	N/A
Dangerous Goods Class	N/A

## Refer to Material Safety Data Sheet for precautions and personal protection.

Disclaimer: Any advice, recommendation, information, assistance or service provided by application is in good faith and is believed by AD-TEK PTY LTD to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by AD-TEK PTY LTD is provided without liability.