

Evencure AC

Acrylic curing compound



FEATURES

Evencure AC is an acrylic modified emulsion used as a curing membrane on freshly poured concrete.

Evencure AC will remain bonded to the substrate and is suitable for use under tiles, screeds and other flooring systems.

Evencure AC meets the requirements of AS3799 and may also be used as a light duty clear concrete sealer.

ADVANTAGES

- Totally water based
- Complies to AS3799
- Single component
- Reduces plastic shrinkage
- Environmentally friendly
- Can be applied by brush, roller or spray
- Will not yellow in sunlight
- Eliminates the need for curing by ponded water, damp hessian or plastic sheeting
- Water wash up
- Accepts most after trades

USES

- Curing compound for all types of concrete. Indoors or outdoors, smooth or textured.
- Suitable as a light duty (foot traffic) protective coating, will whiten slightly in wet weather.
- Not suitable for cars or for use under heavy duty or solvent-borne protective coatings

SPECIFICATION DATA

Appearance:	Transparent solution
Coverage:	5m ² per litre
Finish:	Clear semi gloss
Trafficable:	24 hours
Application temp:	8-35°C
Solids:	34-36% by weight
Cleanup:	Water
Packaging:	20L, 200L, 1000L
Storage:	Store between 5°C - 40°C away from direct sunlight
Shelf life:	12 months

DIRECTIONS FOR USE

Evencure AC can be applied as soon as the bleed water has evaporated and the concrete surface is hard enough to not be marked during the application process. Best applied by spray but roller and brush application is also suitable for small areas.

Wash equipment immediately after use with water.

SAFETY

Refer to the MSDS, contains no hazardous substances requiring labelling

CRG

CRG Pty Ltd
www.crg.solutions

Disclaimer

This is not a specification, and all the information is given in good faith. Since conditions of use are beyond the control of the manufacturer, information contained herein is without warranty, implied or otherwise, and final determination of the suitability of any information or material for the use contemplated, the manner of use and whether there is any infringement of patents is the sole responsibility of the user. The manufacturer does not assume any liability in connection with the use of the product relative to coverage, performance or injury. For application in special conditions, consult the manufacturer for detailed recommendations.