

Floseal

Fluoropolymer Oil and
Water Repellent Sealer



DESCRIPTION

Floseal is a fluoropolymer based protective sealer which penetrates deeply into the substrate to produce an oil repellent barrier. This treatment produces a dry-look finish that significantly reduces the absorption of water and oil allowing spills to be cleaned quickly before they are able to penetrate and stain.



Water, Vegetable oil, mineral oil

BENEFITS

- UV stable
- Water vapour permeable
- Will not yellow or discolour
- Low dirt pick up rate
- Reduces maintenance costs - floor is easier to maintain, sweep and/or mop clean.
- Dust proofs the concrete surface
- Good resistance to traffic
- Can be used on indoor or outdoor surfaces

USES

- Absorbent stone surfaces
- Warehouse floors
- Coloured concrete
- Exposed aggregate concrete
- Carparks, ground level and multi story
- Coloured or plain concrete pavers

TECHNICAL DATA

Finish	Clear neutral
Coverage	0.5 - 3m ² per litre
Flash point	35 - 40°C
Dry time	Tack free 1 - 3 hours

SURFACE PREPARATION

All surfaces to be coated should be dry, free of oil, grease, rust stains, tyre marks, algal growth, loose paint or any other foreign matter.

Where biological contamination exists such lichen, moss, fungus or algae, it should be removed thoroughly and the surface should be treated with a commercially available pre-treatment. The surface must be thoroughly dry before coating.

Newly laid concrete should be allowed to cure for at least 14 days before application.

APPLICATION

Floseal may cause discolouration on some substrates, Apply a small test area first.

Apply only one coat at 0.5 - 3m² per litre depending on the porosity of the substrate.

Low pressure spray or flood coating are the preferred application methods.

CLEANING

Clean all equipment with Hardtop solvent after use.

www.crg.solutions

Whilst any information and/or specification contained herein is to the best of our knowledge, true and accurate, no warranty is given or implied in connection with any recommendations or suggestions made by us, our representatives, agents or distributors.

Floseal

Fluoropolymer Oil and
Water Repellent Sealer

LIMITATIONS

Floseal may change the colour of some substrates and should be tested before prior to full application

The oil repellent nature of **Floseal** makes it unsuitable for use under other coatings.

SAFETY

This material is flammable.
Read the MSDS for this product before use.

Always wear suitable protective clothing and eye protection. Use in a well ventilated area.

www.crg.solutions

Whilst any information and/or specification contained herein is to the best of our knowledge, true and accurate, no warranty is given or implied in connection with any recommendations or suggestions made by us, our representatives, agents or distributors.