

Hardtop ASB

Solvent acrylic concrete sealer



DESCRIPTION

Hardtop ASB is a premium grade co-polymer concrete sealer manufactured from a blend of acrylic resins UV stabilisers and aromatic solvents held in solution.

When dry, **Hardtop ASB** produces a wet look gloss finish which not only protects but also enhances the appearance of plain and coloured concrete.



BENEFITS

- UV stable
- Will not yellow or discolour
- Eliminates oil and grease penetration
- Gloss finish
- Easily recoatable
- Extremely low dirt pick up rate
- Reduces maintenance costs - floor is easier to maintain, sweep and/or mop clean.
- Hardens and dust proofs the concrete surface
- Good resistance to abrasive traffic e.g. forklifts, trucks, cars, foot traffic etc.
- Can be used on indoor or outdoor surfaces

USES

- Imitation slate pattern paving
- Imitation brick pattern paving
- Stamped concrete
- Warehouse floors
- Coloured concrete
- Exposed aggregate concrete
- Carparks, ground level and multi story
- Coloured or plain concrete pavers
- Suitable for all concrete surfaces

TECHNICAL DATA

Finish	Clear gloss
Viscosity	<100 cps
Flash point	26°C
Dry time	Tack free 1 - 3 hours Light traffic 24 hours Heavy traffic 3 days
Volume solids	22 - 23%

SURFACE PREPARATION

All surfaces to be coated must be dry and free of oil, grease, rust stains, tyre marks, algal growth, loose paint or any other foreign matter.

Where biological contamination exists such lichen, moss, fungus or algae, it should be removed thoroughly and the surface should be treated with a commercially available pre-treatment. The surface must be thoroughly dry before priming.

Newly laid concrete should be allowed to cure for at least 14 days.

APPLICATION

Apply a minimum 2 coats of at 8-10 m² per litre.

Where a semi gloss finish is desirable dilute Hardtop ASB with 40% Hardtop cleaner before application

Allow 1-3 hours between coats.

CLEANING

Clean all equipment with **Hardtop cleaner** after use.

www.crg.solutions

Whilst any information and/or specification contained herein is to the best of our knowledge, true and accurate, no warranty is given or implied in connection with any recommendations or suggestions made by us, our representatives, agents or distributors.

Hardtop ASB

Solvent acrylic concrete sealer

LIMITATIONS

Hardtop ASB has limited resistance to solvents

Hardtop ASB is compatible with most types of paints and adhesives but a test area for approval is recommended.

Not suitable for use under cementitious toppings, renders or repair materials. Before using these types of materials Hardtop ASB must first be removed mechanically.

Do not use in areas subject to back water pressure or where high vapour transmission rates are likely.

SAFETY

Read the MSDS for this product before use.

Always wear suitable protective clothing and eye protection. Use in a well ventilated area.

Hardtop ASB is flammable. Keep away from all possible ignition sources. In the event of fire use CO₂ or foam. Do not use a water jet.

www.crg.solutions

Whilst any information and/or specification contained herein is to the best of our knowledge, true and accurate, no warranty is given or implied in connection with any recommendations or suggestions made by us, our representatives, agents or distributors.